RENOGY REGO 12V 400Ah **Lithium Iron Phosphate Battery**

Time to meet the latest Renogy REGO 12V 400A Lithium Iron Phosphate Battery, 5.12kWh massive capacity able for expansion, provide more power than ever before. Manufactured with top-grade cells, the battery provides an exceptional lifespan of more than 6000 cycles. Advanced BMS provides ultra-reliability and safety, and leads smart batteries to the next era. With built-in intelligent self-healing, keep the stable charging performance of the



Key Feature

More Power, Less Installation Space Advanced BMS, Ensure Unprecedented Reliability and Safety Intelligent Self-Heating Function, More Stable Performance Specially Design for Vehicle Use Guaranteed Quality, Certified Performance

Product Specification

GENERAL DATA

Model	RBT12400LFPL-SHBT
Battery Type	Lithium Iron Phosphate
Peukert Exponent	1.01
Connection Method	Parallel (Up to 8)
Communication Protocol	RV-C (CAN Communication Ports), MODBUS (Bluetooth Module)
Input/Output Connector	Anderson 350 Connector
Housing Material	Aluminum
Certifications	MSDS、UN38.3、FCC
Protection Rating	IP65
Dimensions	18.0 x 13.0 x 10.5 inch /457 x 329 x 267.2 mm
Weight	112.4 lbs/51 kg





CHARGER DATA

Nominal Voltage	12.8V
Rated Capacity	400Ah (0.2C, 25°C)
Boost Voltage	14.4V
Float Voltage	N/A
Equalization Voltage	N/A
Maximum Charge Current	5A (-20°C~0°C) 200A (0°C~15°C/50°C~55°C) 300A (15°C~50°C)
Maximum Discharge Current	350A (-20°C~60°C)
Cycle Life	6000 Cycles (80%DOD,70%EOL,0.5C,77 F/25°C)
Charge Temperature Range	32°F~131°F (0°C~55°C)
Discharge Temperature Range	—4°F~140°F (-20°C~60°C)
Storage Temperature Range	Less Than 1 Week: -22°F~140°F (-30°C~60°C) Less Than 6 Months: -4°F~113°F (-20°C~45°C)
Operation Relative Humidity	5%~95%
Self-Discharge Rate	≤1.5%/Month (Shelf Mode)
Internal Resistance	<10mΩ
Tail Current	20A

Compatible Accessories

Sensors	Battery Temperature Sensor (Model: RTSCC) Battery Voltage Sensor (Model: RVSCC)
---------	---